

November 7, 2002
USSN. 09/308,962
Examiner: PECHHOLD, ALEXANDRA K
Group A.U.: 3671

In the Claims

Claims 15-37 are pending in the application.

Please amend the claims as follows:

Clean Version

15. (Three times amended) A method for increasing the bearing capacity of foundation soils for built structures comprising: providing a plurality of holes spaced from each other deep in the foundation soil; injecting into the foundation soil, through said holes, a substance which expands as a consequence of a chemical reaction; producing compaction of the foundation soil contiguous to the injection zone due to the expansion of said substance injected into the soil; constantly monitoring level variations of the soil and/or built structures overlying the injection zone to detect the moment when the built structures and/or the soil surface, overlying said injection zone, begins to raise which is the moment in which the compaction of the foundation soil has reached levels generally higher than a required minimum value at which the soil lying below and around said injection zone withstands and rejects dynamic and static weights exerted thereon by said built structures and by overlying and adjacent soil masses, and wherein the expansion of the injected substance is very fast with a potential increase in volume of the expanded substance being at least five times the volume of the substance before expansion.

33. (Amended) A method for increasing the bearing capacity of foundation soils for built structures comprising:

- providing a plurality of holes spaced from each other deep in the foundation soil;
- providing an expandable substance with very fast expansion time and with a potential increase in volume of the expanded substance being at least five times

November 7, 2002

USSN. 09/308,962

Examiner: PECHHOLD, ALEXANDRA K

Group A.U.: 3671

- the volume of the substance before expansion;
- injecting into the soil, through said holes, said substance which expands as a consequence of a chemical reaction;
 - producing compaction of the soil contiguous to the substance injection zone through expansion of said substance injected into the foundation soil until the soil compaction reaches levels which are generally higher than a minimum compaction value required to provide a bearing capacity of the foundation soil suitable to withstand any dynamic and static weight exerted thereon by the built structures and by overlying and adjacent soil masses; and
 - determining attainment of said minimum compaction value required by constantly monitoring level variations of the soil surface and/or of the built structure overlying said injection zone to detect a moment when the built structure and/or the soil surface, overlying said injection zone, begins to raise, which is the moment when the soil lying below and around said injection zone withstands and rejects upwardly the dynamic and static weight exerted thereon by said built structures and overlying and adjacent soil masses.

November 7, 2002

USPN. 09/308,962

Examiner: PECHHOLD, ALEXANDRA K
Group A.U.: 3671**Marked-up version showing the changes made**

15. (Three times amended) A method for increasing the bearing capacity of foundation soils for built structures comprising: providing a plurality of holes spaced from each other deep in the foundation soil; injecting into the foundation soil, through said holes, a substance which expands as a consequence of a chemical reaction; producing compaction of the foundation soil contiguous to the injection zone due to the expansion of said substance injected into the soil; constantly monitoring level variations of the soil and/or built structures overlying the injection zone to detect the moment when the built structures and/or the soil surface, overlying said injection zone, begins to raise which is the moment in which the compaction of the foundation soil has reached levels generally higher than a required minimum value at which the soil lying below and around said injection zone withstands and rejects dynamic and static weights exerted thereon by said built structures and by overlying and adjacent soil masses, and wherein the expansion of the injected substance is very fast with a potential increase in volume of the expanded substance being at least five times the volume of the substance before expansion.

33. (Amended) A method for increasing the bearing capacity of foundation soils for built structures comprising:

- providing a plurality of holes spaced from each other deep in the foundation soil;
- providing an expandable substance with very fast expansion time and with a potential increase in volume of the expanded substance being at least five times the volume of the substance before expansion;
- injecting into the soil, through said holes, said substance which expands as a consequence of a chemical reaction;
- producing compaction of the soil contiguous to the substance injection zone through expansion of said substance injected into the foundation soil until the soil

November 7, 2002
USSN. 09/308,962
Group A.U.: 3671

Examiner: PECHHOLD, ALEXANDRA K

compaction reaches levels which are generally higher than a minimum compaction value required to provide a bearing capacity of the foundation soil suitable to withstand any dynamic and static weight exerted thereon by the built structures and by overlying and adjacent soil masses; and

-determining attainment of said minimum compaction value required by constantly monitoring level variations of the soil surface and/or of the built structure overlying said injection zone to detect a moment when the built structure and/or the soil surface, overlying said injection zone, begins to raise, which is the moment when the soil lying below and around said injection zone withstands and rejects upwardly the dynamic and static weight exerted thereon by said built structures and overlying and adjacent soil masses.